



WASHER - Installation Specification **Quick Reference L-Series**

Revised 5/01/08

Model	L1030	L1040	L1050	L1075	L1125
Cabinet Width (ins)	30	34	34	43	56
Cabinet Height (ins)	50	57	57	57	69
Cabinet Depth (ins)	36	43	46	46	55
Weight Crated (lbs)	560	992	1036	1502	2734
Weight Net (lbs)	492	838	889	1314	2426
Cylinder Diameter (ins)	23	27.5	27.5	35.5	42.5
Cylinder Depth (ins)	18	18.5	21.5	20	23.5
Cylinder Cu ft	4.2	6.3	7.4	11.2	19.4
RPM Wash	48	45	48	40	34
RPM Spin E4 CR	480	450	450	510	465
RPM Spin E4 SR	480	515	515	510	465
G's Wash	0.75	0.79	0.79	0.8	0.7
G's Spin E4 CR	75	79	79	131	130
G's Spin E4 SR	75	103	103	131	130
Motor HP Wash (1 phase)	0.3	0.33	0.45	N/A	N/A
Motor HP Spin (1 phase)	1.5	1.5	2	N/A	N/A
Motor HP Wash (3 phase)	0.3	0.45	0.57	0.9	1.9
Motor HP Spin (3 phase)	1.5	2	2.7	3.5	5
FLA Wash (1 phase)	3.3	4.4	4.4	N/A	N/A
FLA Spin (1 phase)	8.5	10	10	N/A	N/A
FLA Wash (3 phase)	2.5	3.6	5.1	4.9	10
FLA Spin (3 phase)	5.8	7.4	8	11.6	15
208-240/60/1 Circuit protection	20	30	30	N/A	N/A
208-240/60/3 Circuit protection	15	15	25	25	40
440-480/60/3 Circuit protection	10	N/A	15	15	25
Motor Overloads Auto	Yes	Yes	Yes	Yes	Yes
Motor Overloads Manual	No	No	No	No	Yes
Drain Opening (ins)	2	3	3	3	3
Drain Height C/L (ins)	11	11.5	11.5	3.75	4.25
Water Connection (ins)	0.75	0.75	0.75	0.75	1
Water Pressure (psi)	7-90	7-90	7-90	7-90	7-90
Water Flow GPM	16	16	16	16	27
Door Opening (ins)	13.5	15.75	15.75	21.6	21.6
Door Height (ins)	20.5	24	24	16.5	24.4
KW Standard 1 phase	1.2	1.6	1.6	N/A	N/A
KW Standard 3 phase	1.2	1.5	2	2.7	3.5
KW With Electric Heat	11.4	N/A	18.4	21.7	34.3
Steam Connection (optional)	0.5	N/A	0.5	0.5	0.75
Steam Pressure (psi)	30-90	N/A	30/90	30-90	30-90
Steam Flow (lbs/hr)	90	N/A	130	220	400
Floor Requirements (ins)	6	6	6	12	18
Anchor Bolt Size (ins)	0.5	0.56	0.56	0.56	0.88

This Installation Quick Reference is intended only as a reference source to determine the adequacy and feasibility of a prospective site for installation of Continental-brand equipment. It is not to be utilized as a product or repair manual. In the event that you have questions or concerns regarding the maintenance or repair of a Continental-brand machine, reference should be made to the product and parts manuals for the machine as well as circuit protection instructions (electrical wiring schematics) for that machine. In addition, you can address your questions and concerns directly to our Technical Support Staff by calling our toll-free number: (800) 256-1073, outside the U.S. (920) 231-8222.